

PUNKTY GŁÓWNE DRÓG (sięgaczy)

ODCINEK	WIERZCHOŁEK				kąt zwrotu	ŁUK KOŁOWY		
	P-kt	Kilometraż	X	Y		R	T	Z
Sięgacz W1	A1	0+000,00	6532465.0703	5984059.4927				
	A1.1	0+022,18	6532483.8237	5984071.8541	11,5406°	100	10,11	0,51
	A1.2	0+048,00	6532501.9679	5984089.9548	12,8221°	50	5,62	0,31
	B1	0+069,87	6532520.5163	5984101.5945	x			
Sięgacz W2	A2	0+000,00	6532465.0703	5984059.4927	x			
	A2.1	0+023,43	6532483.8237	5984071.8541	8,5566°	150	11,22	0,42
	A2.2	0+048,00	6532501.9679	5984089.9548	8,8768°	150	11,64	0,45
	B2	0+067,64	6532520.5163	5984101.5945	x			
Sięgacz W3	A3	0+000,00	6532500.0016	5983992.8407	x			
	B3	0+067,86	6532559.2410	5984025.9365	x			
Sięgacz W4	A4	0+000,00	6532510.8256	5983960.8891	x			
	B4	0+066,23	6532573.2969	5983982.8753	x			
Sięgacz W5	A5	0+000,00	6532518.8804	5983923.0031	x			
	B5	0+070,30	6532585.4393	5983945.6613	x			
Sięgacz W6	A6	0+000,00	6532522.0923	5983885.2606	x			
	A6.1	0+039,39	6532561.3196	5983885.9823	6,0394°	200	10,55	0,28
	B6	0+076,45	6532598.2674	5983890.5697	x			
Sięgacz W7	A7	0+000,00	6532521.7630	5983843.5643	x			
	A7.1	0+044,48	6532565.8169	5983842.1199	9,9089°	180	15,6	0,68
	B7	0+084,45	6532605.8574	5983843.5643	x			
Sięgacz W8	A8	0+000,00	6532519.7747	5983813.1944	x			
	A8.1	0+022,02	6532565.1585	5983798.3629	7,4929°	150	9,82	0,32
	A8.2	0+047,80	6532565.1585	5983798.3629	9,4791°	150	12,44	0,57
	B8	0+091,80	6532609.0066	5983794.5327	x			
Sięgacz Z1	C1	0+000,00	6532345.2436	5984006.8951	x			
	C1.1	0+060,52	6532403.5025	5984023.2271	0,4935°			
	C1.2	0+079,40	6532421.9981	5984028.5690	9,9089°	60	6,86	0,45
	D1	0+117,42	5984028.5690	5984047.0039	x			
Sięgacz Z2	C2	0+000,00	6532350.4517	5983964.6617	x			
	C2.1	0+078,84	6532426.6460	5983984.9552	8.6383°	60	6,86	0,45
	D2	0+134,02	6532477.2413	5984047.0097	x			
Sięgacz Z3	C3	0+000,00	6532356.4384	5983916.2686	x			
	D3	0+0145,77	6532493.6044	5983965.5887	x			
Sięgacz Z4	C4	0+000,00	6532405.3455	5983885.4990	x			
	Z4a	0+026,94	6532430.9083	5983893.9435	x			
	Z4b	0+064,52	6532466.5887	5983905.7303	x			
	D4	0+0104,06	6532504.1382	5983918.1345	x			
Półkole Z4a-Z4b	zestawiono na stronie				x			
Sięgacz PI	R	0+000,00	6532358.5549	5983878.0259	x			
	R1	0+084,50	6532348.3422	5983961.6969	1,3459°			
	S1	0+131,22	6532341.5551	5984008.1978	x			
Łącznik Ł1	K	0+000,00	6532315.2604	5983803.7898	x			
	K1.1	0+009,58	6532324.8905	5983802.7423	68,7578°	skrzyżowanie		
	K1.2	0+053,40	6532345.0789	5983842.0706	17,3130°	60	9,13	0,69
	K1.3	0+101,30	6532379.8873	5983876.8873	27,2335°	60	14,53	1,74
	L	0+128,45	6532405.3455	5983885.4990	x			